

DOL 114 0-5 V

Humidity and Temperature Sensor



1 Product description

DOL 114 is a high-precision humidity sensor for measuring relative humidity and temperature. It is intended for application in livestock houses but is also well suited for a number of industrial applications.


The sensor features two analogue outputs with very low output resistances and full protection against short circuits and wiring failures.

The special sensor element and the built-in filter enable application in livestock houses with constantly high humidity. The sensor ships with a built-in connector or cable, and with a specific adapted specification area - all according to your needs.

The sensor is microprocessor-controlled and has a two-color light emitting diode (LED) to communicate the operation status and the error diagnostic.

Sensor can be supplied with blinded LED for applications where this is needed.

2 Mounting guide



For optimum mounting of the sensor, use mounting clip or mount it free-hanging in the cable.

The sensor element of the sensor requires free air passage.

Mount the sensor so it is not exposed to direct sunlight, as this would affect the measurement.




- Remember to put on a protection cap before mounting the cable.

3 Installation guide



Installation, servicing and troubleshooting of all electrical equipment must be carried out by qualified personnel in compliance with the applicable national and international standard EN 60204-1 and any other EU standards that are applicable in Europe.

3.1 Connection of the sensor



Signals and wire colors

DOL 14		DOL 14 HQ		DOL 114 0-5 V
(BK) Black = +13-24 V DC	→	(WH) White = +13-28 V DC	→	(BN) Brown = +11-30 V DC
(BN) Brown = 0...10 V/%RH	→	(GN) Green 0...10 V/%RH	→	(WH) White = 0...5 V/%RH
No temperature output	→	No temperature output	→	(BK) Black = 0...5 V/°C
(BU) Blue = GND (0 V)	→	(BN) Brown = GND (0 V)	→	(BU) Blue = GND (0 V)

LED/LIGHT PROTOCOL		Functional graph	
LED	Status		
Green	Red		
ON			Operation OK
Flash			Outside normal range (below 10 % RH or exceeding 95 % RH)
	ON		Connection error Load < 500 Ω
	Flash		Sensor defect Over or under voltage alarm Overload

4 Maintenance

When cleaning and disinfecting the house, the protective cap must be put on the sensor so that it hangs with the tip up, as shown in the picture.

Alternatively, the sensor must be removed from the house and the cable's M12 sealing plug installed.

- Sensor is cleaned with:
- Water and brush
 - High-pressure cleaning with cold water (only with attached protective cap)



Avoid using:

- High-pressure cleaning with hot water
- Highly compressed air
- Solvents
- Corrosive/caustic agents
- Alcohol-based disinfectants

After the sensor has been exposed to water and condensation, it requires a period where the relative humidity is lower than 80 %RH in order for it to measure correctly.



Do not bend the sensor as this would inflict permanent damage on the electronics of the sensor.

4.1 Recycling/Disposal



The label indicates that the product must not be disposed of as general refuse disposal and must be treated as electronic waste.



The label indicates that the product is suitable for recycling.

It must be possible for customers to deliver the products to local collection sites/recycling stations in accordance with local instructions. The recycling station will then arrange for further transport to a certified plant for reuse, recovery and recycling.

5 Technical data

		Humidity measurement	Temperature measurement
Specifications			
Measuring range		0 - 100% RH	- 40 °C – +60 °C
Accuracy		± 3 % RH (40–85 %) ± 4 % RH (10-95 %) at 0-40 °C	± 0.6 °C (+10 – +40 °C) ± 1.5 °C (- 30 – +60 °C)
Output signal		0.05 V/% RH	0.05 V/°C; 0 °C at 2 V
Time constant T ₆₃		20 s at 0.5 m/s air speed	6 min. at 0.5 m/s air speed
Common			
Electrical			
Supply voltage	V DC	11 - 30	
Current	mA	12 mA no load 35 mA max. load	
Load	Ω	> 500 Ω - < 10 MΩ	
Recommended load	Ω	≥100 kΩ	
Max. output current	mA	20	
Output impedance	Ω	< 1	
Mechanical			
Cable dimensions	AWG	2 m 4 x 22 AWG / 0.34 mm ²	
Max. Cable length at 0.75 mm ²	m	100	
Max. Cable length at 1.50 mm ²	m	200	
Environment			
Temperature, operation	°C	- 40 °C – +60 °C	
Protection class	IP	67	
Shipment			
Packing dimensions H x W x D	mm	275 × 200 × 20	
Shipment weight ex. connector	g	150	

5.1 Dimensions

Dimensions in mm.

